

# **DIY Acrylic Stud Adhesive**

Gyprock DIY Acrylic Stud Adhesive is a simple and easy to use water soluble adhesive that adheres plasterboard sheets to timber wall studs and ceiling joists as well as metal framing members. It is specially formulated to offer excellent adhesion properties and is easily identified, once installed, by its distinctive blue colour.

## **Recommended Use**

DIY Gyprock Acrylic Stud Adhesive is used for adhering plasterboard and fibre cement wallboard to timber or steel frames. It is recommended to use DIY Acrylic Stud Adhesive with Gyprock Repair Panels for minor repair and maintenance applications. It is suitable for use with prepainted metal battens and some treated timber in residential applications. Stud adhesive should be used in conjunction with nail or screw fasteners to constitute a functional fixing system.



# **Product Features**



### **DIY Range**

Professional quality in convenient pack sizes



#### **Superior Adhesion**

Good initial grab and excellent adhesion properties



Easy Application

Apply with a stud adhesive applicator



### Australian Made

Licensed by Australian Made Campaign Ltd

Gyprock DIY Acrylic Stud Adhesive	
Specifications	
Feature	Description
Colour	Blue
Packaging	1kg re-sealable pail
Shelf Life	12 months from date of
	manufacture
Specific Gravity	1.3-1.7
VOC Content (as specified by GBCA)	22g/L as VOC content per material
Product Manufacture	DIY Acrylic Stud Adhesive is manufactured by CSR Gyprock in Australia and made to stringent product specifications.

# Important

- DO NOT use DIY Acrylic Stud Adhesive on Tiled Wet Area Systems.
- DO NOT rely on stud adhesive in Fire Rated systems.
- Daubs of adhesive must never coincide with fastener points.
- DIY Acrylic Stud Adhesive should not be used when the temperature is less than 5°C.
- Fix board within 20 minutes of applying adhesive to the frame.
- If liquid has separated from compound, re-mix before use.
- Ensure surfaces are free from oil, grease or other foreign materials before use.
- Always use clean tools.
- Replace lid when not in use.

# Storage

Store buckets of compound in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.



### Application

- Apply Acrylic Stud Adhesive to the studs with a broadknife, using enough material to form 'walnuts' of adhesive 25mm in diameter and 15mm high.
- Apply walnut sized daubs of adhesive at 300mm max (for wall applications), 230mm max (for ceiling applications), and 200mm min centres from the nailing points at sheet edges and no closer than 200mm fixing points.
- Press Gyprock plasterboard against frame and hold in place for 24 hours by screws through a temporary Gyprock block at the centreline of the sheet on every second stud.

### **Installing to Standards**

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outlines the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

### **Health and Safety**

Refer to the Safety Data Sheet for this product which is available from <u>www.gyprock.com.au</u> or contact:

CSR Gyprock Triniti 3, 39 Delhi Rd, North Ryde NSW 2113 Australia Phone:**131 744** New Zealand Phone: **0800 277 123** 

### Resources

For further information on this product please visit <u>www.gyprock.com.au</u> or refer to the Gyprock Red Book. For technical support, contact:



PHONE: 1800 621 117

### **Manufactured For Life Warranty**

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto www.gyprock.com.au/warranty, or contact us on **1300 306 556**.



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.