

The natural stone look



Get the natural stone look

PGH Stone is our collection of manufactured stone veneer products that offer a great alternative to wall tiles and other forms of cladding, where a unique, natural stone look and feel is the desired finish. Suitable for internal and external use, PGH Stone provides a personal touch to your home, or adds character to commercial settings.

Cast from moulds created using actual stone pieces, PGH Stone displays the same textures, colours and patterns found in real stone masonry. Available in a selection of natural-looking stone finishes and formats, there will be a product to suit many different project needs. Give your residential or commercial project a beautiful, natural, tactile feature with PGH Stone.

PGH Stone is manufactured sustainably


The manufacturer of PGH Stone commits to sustainability by reducing waste and conserving resources during production. It recycles the wastewater from its manufacturing process and crushes imperfectly manufactured products to repurpose the material.

Benefits of PGH Stone

PGH Stone is made in Australia, does not require painting or coating and can be used indoors or outdoors. It is backed by CSR, has minimal maintenance long-term and comes with a **manufacturer's warranty of 15 years.**

PGH Stone product colour variations

Our hand-crafted products are made with reconstituted sandstone utilising naturally occurring aggregates, therefore no guarantee can be given that PGH Stone hand crafted at different times will be identical in colour shade.



WITHOUT MORTAR

CLASSIC LEDGESTONE

A typical rectangular appearance that is easy to install

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



WHITEHAVEN



NATURAL FIELDSTONE

A rough and irregular texture allowing for a variety of unique looks

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



WHITEHAVEN



RUGGED LEDGESTONE

A larger and more rounded appearance, resembling real field stones

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



WHITEHAVEN



WITH MORTAR


CLASSIC LEDGESTONE

A typical rectangular appearance that is easy to install

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



NATURAL FIELDSTONE

A rough and irregular texture allowing for a variety of unique looks

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



RUGGED LEDGESTONE

A larger and more rounded appearance, resembling real field stones

ALPINE GREY



RUSSET



GILDED SAND



SILVER PEAK



Capping Stones are available to suit all products and colours.



CORNER STONES FOR EACH COLOUR:

CLASSIC LEDGESTONE



Alpine Grey



Russet



Gilded Sand



Silver Peak



Whitehaven

NATURAL FIELDSTONE



Alpine Grey



Russet



Gilded Sand



Silver Peak



Whitehaven

RUGGED LEDGESTONE



Alpine Grey



Russet



Gilded Sand



Silver Peak



Whitehaven

3 FORMATS
5 NATURAL COLOUR OPTIONS



| | Classic Ledgestone | Natural Fieldstone | Rugged Ledgestone | Capping Stone |
|--------------------------|---|--|---|---------------|
| Carton Weight (kg) | 30 (flats) / 23 (corners) | 30 (flats) / 23 (corners) | 30 (flats) / 23 (corners) | 13kg each |
| Cartons/Pallet | 32 (flats) / 32 (corners) | 24 (flats) / 32 (corners) | 32 (flats) / 32 (corners) | 80 per pallet |
| Weight/Pallet (kg) | 960 (flats) / 736 (corners) | 888 (flats) / 576 (corners) | 1024 (flats) / 768 (corners) | 1040kg |
| M ² /Carton | 0.42m ² (flats) / 1.00Lm (corners) | 0.6m ² (flats) / 1.20Lm (corners) | 0.42m ² (flats) / 1.00Lm (corners) | n/a |
| Height (mm) | 35–160 | 50–355 | 35–160 | 280–300 |
| Length (mm) | 100–530 | 100–450 | 100–530 | 490–510 |
| Thickness (mm) | 25–65 | 25–65 | 25–65 | 35–45 |
| Corner Short Return (mm) | 50–105 | 65–100 | 40–135 | N/A |
| Corner Long Return (mm) | 70–260 | 150–280 | 100–320 | N/A |
| Corner Height (mm) | 60–145 | 170–250 | 40–120 | N/A |





RUGGED LEDGESTONE:
RUSSETT

NATURAL FIELDSTONE:
ALPINE GREY

CLASSIC LEDGESTONE:
GILDED SAND



NATURAL FIELDSTONE:
GILDED SAND

Composition

PGH Stone is made from sand, cement, additives, and water. Cast from moulds created using actual stone pieces, PGH Stone displays the same textures, colours and patterns found in real stone masonry. Available in a selection of natural-looking stone finishes and formats, there will be a product to suit many different project needs.

Technical Information


| Property | Value |
|--------------------------------|------------------------|
| Compressive Strength | <21MPa |
| Cold Water Absorption (CWA) | 6.10% |
| Avg. Heat Release Rate | FTI (Failed to Ignite) |
| Avg. Specific Extinction Area | 4.7m²/kg |
| Product Group | Group 1 |
| Product Warranty | 15 year (limited) |
| Product Usage (Non-structural) | Interior & Exterior |

| Product Weight | |
|--------------------|-----------------------------|
| Classic LedgeStone | Between 57kg to 62kg per m² |
| Natural Fieldstone | Between 48kg to 62kg per m² |
| Rugged LedgeStone | Between 48kg to 53kg per m² |

Estimating stone required

To determine the amount of PGH Stone Flat pieces needed, measure the area to be covered. Measure the length and height to arrive at the gross m² of flat stone needed [length (m) x height (m)]. Subtract m² for corners (if applicable), windows, doors, or other openings.

To determine the amount of corner pieces needed, measure the outer vertical edge in linear metres. Corners occupy approx. 0.2m² of wall space per linear metre of product, so this number can be subtracted from the requirement for Flat pieces.



Note: PGH Stone is sold in cartons containing 0.42–0.60m² of loose pieces (Flats) and cartons containing 1.0–1.2Lm of loose pieces (Corners). Individual stone pieces within boxes may vary depending on the selected profile, so review of the stone pieces prior to installation is recommended.

Application

Utilising PGH Stone in a walling application requires bonding to a solid substrate such as a concrete or masonry wall. PGH Stone is not suitable to stand on its own, or on a non-structural element such as plasterboard. For height and wind load limit on wall applications, consult adhesive manufacturers for more information. PGH highly recommends that all standards and specifications be independently checked by the project designer(s), as well as the sealant and adhesive manufacturers for recommendations to suit the specific requirements of each project.

Tips to consider

Building code compliance
Building code requirements may vary from area to area. Check with local authorities for the requirements in your area.

Corner installation
If your application requires corner pieces, start by installing a corner piece first, followed by the adjoining flat pieces. Note that the corner pieces may experience greater wind load.

It is recommended that corners be strengthened through continuous metal mesh wrap with min. 450mm at outside and inside corners, fastened at a framing member. Where lapping of expanded metal mesh is required, follow the manufacturer's instructions for the minimum lapping length.

Fire safety
Concrete is listed as a non-combustible material under the National Construction Code. Consult the adhesive manufacturer for a suitable product if you intend to use PGH Stone in a fire-resistant area such as a fireplace.

Substrate requirement
PGH recommends that wall construction be in accordance with the relevant Australian and industry standards when preparing a surface for stone cladding. The contractor must examine substrates and advise the general contractor and architect of any existing conditions or surface contamination which will require correction before work commences. Before starting, substrates must comply with maximum allowable deflection criteria as called for by Australian industry standards or the applicable local building code. Consult the adhesive manufacturer for the appropriate substrate surface treatment.

Other precautions
To reduce the risk of falls during installation, ensure sufficient time for the adhesive to set before continuing to higher levels. Always follow the adhesive manufacturer's recommendations for staged installation, set times and height limits.

Cutting stone may generate silica dust. It is recommended that appropriate PPE be worn, and dust-reducing cutting methods (i.e. wet saw) are employed.



Visit a PGH Bricks & Pavers Selection Centre

With specially designed selection tools and a wide range of PGH Stone, Bricks & Pavers on display, choosing the ideal materials for your home has never been easier.



Frequently Asked Questions

How do you install PGH Stone?

- Tile adhesive over properly prepared substrate
- Mechanical fixing may be required in certain circumstances
- Please refer to the PGH Stone Cladding Installations Recommendations document available on our website - <https://www.pghbricks.com.au/-/media/pgh-pluto/pluto/brochures/2023-brochures/pgh-stone-installation-recommendations.pdf>

Can I seal PGH Stone?

It is not required to seal PGH Stone. A sealer will provide added protection and will usually be easier to clean if the surface becomes dirty. If you choose to use a sealer for added protection, use a penetrating breathable masonry sealer. NOTE: A sealer may affect the stone colour and may create a gloss or matte finish. Always test a small area beforehand.

What maintenance is required for PGH Stone if any?

Periodic washing to remove surface dust and debris is all that is required. Most PGH Stone products are virtually maintenance free.

How much does it cost to install PGH Stone?

Contact installer for accurate price.

Where can I install PGH Stone?

PGH Stone can be applied to any structurally sound surface with the proper preparation. It fits nearly any building plan — large or small, interior or exterior, new residential or commercial projects — or on any remodel.

Is PGH Stone natural stone?

Our hand-crafted products are made with reconstituted sandstone utilising naturally occurring aggregates, with various advantages over natural stone; its ease of installation, prefabricated corner pieces and caps to suit all products, its availability, more economical to buy than natural stone, colour can be altered to suit personal taste.

What is PGH Stone made of?

PGH Stone is cast from moulds created using actual stone pieces, PGH Stone displays the same textures, colours and patterns found in real stone masonry.

What kind of surface is necessary to apply PGH Stone?

PGH Stone products may be adhered to any prepared clean, untreated, structurally sound wall surfaces. AC/ cement sheeting over timber or steel frame, Masonry and Brick, Tilt/Pre cast panel. Please refer to our installation instructions for further information.

Can we install PGH Stone around a fireplace?

PGH Stone can be installed around a fireplace. The veneer must be a minimum of 20cm from any open flame.

Can PGH Stone products be used on wall area adjacent to swimming pools?

PGH Stone products will perform the same as any other quality reconstituted stone. Although, it should be taken into consideration with any reconstituted stone or natural material, continued exposure to chlorine and other chemicals may eventually affect the colouration of the products. When frequently exposed to water, we recommend protection with a non-film breathable masonry sealer.

NOTE: A sealer may affect the stone colour and may create a gloss or matte finish. Always test a small area beforehand.

How heavy are PGH Stone products?

The approximate weights range from 48kg to 62kg per m² depending on the PGH Stone product selected (exclusive of installation materials).

How is PGH Stone sold?

- The loose stones are packed in corflute outdoor suitable boxes.
- Flats are sold in boxes ranging from 0.42–0.6 per m²
- Corners are sold in boxes ranging from 1–1.2 L/m
- Capping is sold individually

Can PGH Stone products be used on both exterior and interior applications?

Yes! The products are suitable for both applications. They allow you to bring the outdoors inside as well as emphasizing your design and continuity in your colour and texture schemes.

Will PGH Stone products weather?

The base colour is blended throughout, and permanent mineral oxide pigments are applied and absorbed when the veneer is cast. Colour becomes an integral part of the veneer and, like natural stone, there are minimal noticeable colour changes after years of weathering. 15 year warranty against colour fade no greater than 2%.

Should I colour the mortar or grout?

The choice between mortar or grout comes down to personal preference. Either can be used.

- Sand and cement based mortar can be tinted with an iron oxide pigment. This style of application can enhance or accompany the stone colour used.
- Tile grout can also be used to achieve the same outcome. Please refer back to the grout manufacturer for technical assistance.

Can I install PGH Stone myself?

In general, installation of PGH Stone can be installed by almost anyone. However, installation does require a fundamental understanding of stone masonry. For Classic LedgeStone and Rugged LedgeStone, we highly recommend a professional installer. Please refer to our user installation guide.

How important is a good stone installation?

As with any building material, the beauty of the product is greatly enhanced by how well it is installed. PGH Stone, careful consideration regarding the type of profile and colour selected, the actual installed stone "pattern", and the type of grout technique used, are all very important factors to regard. It is always best to create a mock up board with the desired aesthetic appeal prior to installation on your project.

Can PGH Stone products be cut?

Yes, PGH Stone are easily cut or trimmed using a hatchet or wide-mouth nipper. We highly recommend the use of a dustless vacuum saw.

What happens if PGH Stone chips?

Manufactured from crushed sandstone chips tend to blend in with the face colour and add a natural appearance to the stone.

Can PGH Stone be used on water features and walkways?

- Not recommended for walkways due to the undulating finish.
- Not recommended for water features due to water absorption and adhesion.

Is PGH Stone manufactured sustainably?

The manufacturer of PGH Stone commits to sustainability by reducing waste and conserving resources during production. It recycles the wastewater from its manufacturing process and crushes imperfectly manufactured products to repurpose the material.

PGH STONE PRODUCT COLOUR VARIATIONS

Our hand-crafted products are made with reconstituted sandstone utilising naturally occurring aggregates, therefore no guarantee can be given that PGH Stone hand crafted at different times will be identical in colour shade.



To watch our series of videos on how to install PGH Stone click here <https://www.pghbricks.com.au/pgh-stone>



For more information
pghbricks.com.au/pgh-stone
13 15 79



Disclaimer:

Information in this brochure is general only and is not a recommendation to use any of our products. Always obtain specialist advice to ensure our products, and their intended use, meet your requirements. If product images are shown, colours are represented as accurately as possible but we recommend checking your chosen product against a sample (or in a selection centre) before purchasing as digital representations may affect colour tones and finishes. In addition, products (including from batch to batch) and samples may vary regarding colour and surface finish due to manufacturing processes and raw materials used. For further information please contact our Customer Service Centre on 13 15 79.

Warning:

PGH Stone contain crystalline silica. Cutting or grinding these products creates dust, which may be hazardous and should not be inhaled. Please ensure that when cutting or grinding, an approved mask (respirator) is worn. For more information visit: pghbricks.com.au/product-info/working-safely-pgh

© 2024 PGH Bricks & Pavers Pty Ltd ABN 68 168 794 821. All trademarks are the property of their respective owners.

