

Gyprock HD Screw

The Gyprock HD Screw is specifically designed for use on Gyprock high density plasterboards to achieve a professional finish.

Featuring a unique lipped head and reversed thread pattern, the Gyprock HD Screw has the ability to drive through boards with ease and achieve a high-quality finish, with less chance of paper burring or bulging around the head.

Collated in durable plastic strips, the HD Screw is ideal for contractors in both residential and commercial settings to install Gyprock high density plasterboard products efficiently to a professional standard.

The Gyprock HD Screw removes the need to pre-drill pilot holes into high density plasterboards and reduces the risk of 'mushrooming' or 'volcanoing' around the head of screws allowing for easier, high quality installations.



Typical Applications

The Gyprock HD Screw is specifically designed for use on Gyprock high density plasterboards and can be used for both Timber and Steel substrates.

APPLICATION	WALL		CEILING		WALL		CEILING	
Substrate	Softwood/Hardwood		Softwood/Hardwood		Steel (0.5 - 0.8BMT)		Steel (0.5 - 0.8BMT)	
Length	25mm	32mm	25mm	32mm	25mm	32mm	25mm	32mm
Gyprock Soundchek 10mm	✓	✓	✗	✓	✓	✓	✓	✓
Gyprock Soundchek 13mm	✗	✓	✗	✓	✓	✓	✓	✓
Gyprock HD 10mm	✓	✓	✗	✓	✓	✓	✓	✓

Download the [Gyprock HD Screw product flyer](#) for more information.



Resources

For further information on this product please visit www.gyprock.com.au or refer to the Gyprock Red Book. For technical support, contact:

DESIGNLINK™

PHONE: 1800 621 117



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.