





Interior-Timber Frame-Resilient Mount-CSR 2160
FRL -/120/120 OR
60/60/60
(From both sides)



Wall Schedule

Wall Name	Manufacturer	Fire Rating	Acoustic Rating
Interior-Timber Frame-Resilient Mount-CSR2160-150mm	CSR GYPROCK	-/120/120 OR 90/90/90 (From both sides)	ACOUSTIC OPT (A 48/42) (B 56/49) (C 58/49) (D 52/46)
Interior-Timber Frame-Resilient Mount-CSR2160-170mm	CSR GYPROCK	-/120/120 OR 90/90/90 (From both sides)	ACOUSTIC OPT (A 49/43) (B 57/50) (C 59/50) (D 53/47)
Interior-Timber Frame-Resilient Mount-CSR2160-200mm	CSR GYPROCK	-/120/120 OR 90/90/90 (From both sides)	ACOUSTIC OPT (A 50/44) (B 58/51) (C 59/50) (D 53/47)
Interior-Timber Frame-Resilient Mount-CSR2160-220mm	CSR GYPROCK	-/120/120 OR 90/90/90 (From both sides)	ACOUSTIC OPT (A 51/45) (B 58/51) (C 60/51) (D 54/48)

CSR BUILDING PRODUCTS LTD

Head Office: Trinit 3, 39 DELHI RD, NORTH RYDE NSW 2113
LOCKED BAG 1345, NORTH RYDE BC NSW 1670
A.B.N. 55 008 631 356 Ph: 1300 306 556 www.gyprock.com.au

TITLE Interior-Timber Frame-Resilient Mount-CSR2160

SCALE

1:20 @ A4

SHEET SIZE

A4

DRAWN

DL

DATE

13.10.16

SHEET NO.

1 of 1

CHECK

DL

REVISION

A

CSR