



## Gyprock® Stud Adhesive XL

Gyprock Stud Adhesive XL is a simple way to adhere plasterboard sheets to timber wall studs and ceiling joists as well as metal framing members. It is specially formulated to offer superior adhesion and slump resistance. Stud Adhesive XL is easily identified by its distinctive blue colour, while the bulk pack provides greater coverage onsite.

### Recommended Use

Gyprock Stud Adhesive XL is used for adhering plasterboard and fibre cement wallboard to timber or steel frames. It is suitable for use with some treated timber in residential and commercial wall and ceiling applications. Stud Adhesive XL can be hand applied. Stud adhesive should be used in conjunction with nail or screw fasteners to constitute a functional fixing system.

### Important

- DO NOT use Stud Adhesive XL in tiled wet area Systems
- DO NOT rely on stud adhesive in Fire Rated systems
- May not be suitable for use with some pre-painted metal battens
- Daubs of adhesive must never coincide with fastener points
- Stud Adhesive XL should not be used when the temperature is less than 5°C
- Fix board within 20 minutes of applying adhesive to the frame
- If liquid has separated from compound, re-mix before use.
- Ensure surfaces are free from oil, grease or other foreign materials before use
- Always use clean tools
- Replace lid when not in use

### Storage

Store buckets of compound in a dry environment out of direct sunlight. Remove lid and stir prior to use. Unused product should be stored by resealing the original bucket. Remix prior to use. Discard if drying has commenced.



### Product Features




#### Superior Adhesion

Strong initial grab with superior adhesion & slump resistance



#### Easy Application

Apply with a stud adhesive applicator



#### Greater Coverage

Bulk pack for greater coverage



#### Australian Made

Licensed by Australian Made Campaign Ltd

Gyprock (Product) Specifications	
Feature	Description
Colour	Blue
Packaging	10kg re-sealable pail
Shelf Life	12 months
Specific Gravity	1.3-1.7
VOC Content (as specified by GBCA)	37g/L as VOC content per material
Product Manufacture	Gyprock Stud Adhesive XL is manufactured by CSR Gyprock in Australia and made to stringent product specifications.



## Installation

### Timber frames

- Apply Stud Adhesive XL to the studs with a broadknife, using enough material to form 'walnuts' of adhesive 25mm in diameter and 15mm high.
- Apply walnut sized daubs of adhesive at 300mm max (for wall applications), 230mm max (for ceiling applications), and 200mm min centres from the nailing points at sheet edges and no closer than 200mm fixing points.
- Press Gyprock plasterboard against frame and hold in place for 24 hours by screws through a temporary Gyprock block at the centreline of the sheet on every second stud.

Refer to the Gyprock Red Book 2: Residential Installation Guide for **metal frames**.

## Installing to Standards

Installing to Standards AS/NZS2589: Gypsum linings – Application and Finishing outline the procedures for jointing and finishing of Gyprock plasterboard in conjunction with additional details contained in Gyprock Technical Literature.

## Health and Safety

Refer to the Safety Data Sheet for this product which is available from [www.gyprock.com.au](http://www.gyprock.com.au) or contact:

CSR Gyprock  
Trinity 3, 39 Delhi Rd, North Ryde NSW 2113  
Australia Phone: **131 744**  
New Zealand Phone: **0800 277 123**



Licensed by Australian Made Campaign Limited to use the Australian Made Logo.



Gyprock plasterboard products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system.

## Resources

For further information on this product please visit [www.gyprock.com.au](http://www.gyprock.com.au) or refer to the Gyprock Red Book. For technical support, contact:

**DESIGNLINK<sup>™</sup>**

PHONE: 1800 621 117

## Manufactured For Life Warranty

Gyprock products are manufactured for life with all CSR products designed to achieve optimal performance when part of a CSR integrated system. Gyprock continues to lead the market with premium quality products which are the preferred choice of plastering professionals. Gyprock plasterboard products are manufactured to the Australian Standards AS2588 providing confidence in quality of product and support. For details on our product warranty, please log onto [www.gyprock.com.au/warranty](http://www.gyprock.com.au/warranty), or contact us on **1300 306 556**.